## 3-Seat Frame H:2.5m

KSW903



Item no. KSW903-0902		
General Product Information		
Dimensions LxWxH	540x240x274 cm	
Age group	2+	
Play capacity (users)	-	
Colour options		

KOMPAN swings can be configured to adapt individual needs and demands. All A-Frame swings are available in 2.0m and 2.5m height with posts of impregnated pine wood or hot dip galvanized steel. As seats we offer standard swing seat, cradle seat, toddler seat or bird nests with a diameter of ø100cm or 120cm. Further the seats are available with either hot dip galvanized chains or stainless steel chains and if preferred with antiwrap suspensions. The modular swing system also enable multibay configurations with 2, 3, 4 or more sections.





## 3-Seat Frame H:2.5m

KSW903



Item no. KSW903-0902		
Installation Information		
Number of installers	2	
Total installation time	5.9	
Excavation volume	1.95 m³	
Concrete volume	0.00 m³	
Footing depth (standard)	90 cm	
Shipment weight	172 kg	
Anchoring options	In-ground 🗸	
Warranty Information		
Hot dip galvanised steel	Lifetime	
Movable parts	2 years	
Spare parts guaranteed	10 years	



## Sustainability

Cradle to Gate A1-A3

KSW903-0902



Kompan A/S C.F. Tietgens Boulevard 32C DK-5220 Odense SØ Denmark



Validation of CO<sub>2</sub> calculation of: Freestanding play equipment



## Data version no. 2021-09-27

The  $CO_2$  calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: KSW92011-0910.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 15. October 2021 | Valid until: 15. October 2023 Validated by:

Bathar

Bente Hviid, Senior Consultant

Peter Bendtsen, Senior Consultant

Validation based on report: Validation of CO<sub>2</sub> calculation of 8 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Bente Hviid and Peter Bendtsen.

Publication date: 15. October 2021

By Bureau Veritas HSE www.bureauveritas.dk +45 7731 1000



Cycle 1-A3))

Recycled

materials

%

34.80

CO<sub>2</sub>e/kg

kg CO<sub>2</sub>e/kg

2.12

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

**Total CO2** 

emission

kg CO<sub>2</sub>e

345.10