
Product technical sheet


WORKOUT 2326




Product data

| Length | 543 cm | |
|---|--------------|--|
| Width | 344 cm | |
| Total height | 241 cm | |
| Age group | 14+ years | |
| Maximum weight of user | 140 kg | |
| Safety zone | 57,7 m2 | |
| Free fall height | 230 cm | |
| In accordance with norm EN | 16630:2015 | |
| Weight of the heaviest part | 30 kg | |
| Dimensions of the largest part | 10x10x320 cm | |
| Availability of spare parts | YES | |
| Color options | | |
| Data is subject to change without prior notice. | | |









vinci play







Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991

wôrkôut


biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

Material specification





Powder galvanized and powder coated or stainless steel construction of 100 x 100 mm profile,





Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,

Stainless steel bars with a diameter of 38 mm for a comfortable grip during exercises.



Certified handles and calibrated chains made of stainless steel, preventing fingers from getting caught,




Stainless steel screws and/or screws covered with plastic caps,

Safe end caps on top of the structure made of synthetic material,

Additional information

- device intended for public outdoor gyms;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



15 year guarantee - Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



15

5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

Amount of safe surface corresponding with free fall height:

HIC 100 2,6 m² HIC 130 4,3 m² HIC 139 8,6 m² HIC 230 39,3 m²

Data is subject to change without prior notice.


Surfaces EN 16630:2015

| | Description (mm) | Layer thickness (cm) | Maximum fall height (cm) |
|---|-----------------------------------|-------------------------|-----------------------------|
| Concrete / stone / bituminous surfaces (A, B, C) | - | - | ≤100 |
| outer soil layer (A,B,C) | - | - | ≤120 |
| Turf (A,B,C) | - | - | ≤150 |
| bark (A,C) | Particle size from 20 to 80 | 30 | ≤200 |
| | | 40 | ≤300 |
| wood shavings/cuttings (A, C) | Particle size from 5 to 30 | 30 | ≤200 |
| | | 40 | ≤300 |
| sand (A,C) | Particle size from 0,2 to 2 mm | 30 | ≤200 |
| | | 40 | ≤300 |
| gravel (A,C) | Particle size from 2 to 8 | 30 | ≤200 |
| | | 40 | ≤300 |
| attested synthetic (A, B, C) | Tested according to EN 1177 | | 230 |

В

A





4

С

wôrkôut

20

biuro@vinci-play.com info@vinci-play.com www.vinci-play.com

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991

30/04/2021