



Product Service

CERTIFICATE

No. Z2 053696 2921 Rev. 01

Holder of Certificate: **KOMPAN A/S**
C.F. Tietgens Boulevard 32C
5220 Odense SØ
DENMARK

Certification Mark:



Product: **Combination playing construction**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713205773-54

Valid until: 2026-12-19

Date, 2022-03-30

(Tobias Hofmann)

CERTIFICATE

No. Z2 053696 2921 Rev. 01

Model(s): PCM001621, PCM001821, PCM002321, PCM002421
PCM002521, PCM101021, PCM101221, PCM101421
PCM101521, PCM101621, PCM101721, PCM200521
PCM200621, PCM200821, PCM201021, PCM201221
PCM201321, PCM300521, PCM300821, PCM400221
PCM400521, PCM900121

Parameters:

Combination system based on the following components:

Posts made of Ø101,6 mm pre-galvanized and powder coated steel posts alternative Ø100 mm impregnated pine wood.

Green Line Texmade posts made of Ø100 mm plastic/textile.

Side panel made of 19 mm HDPE or impregnated pine wood complete close, with openings in different designs,

with tables, benches, moving play activities or music tubes.

Tube elements like crossbars, tube ladders,

fireman poles and climbing activities made of Ø38 mm and Ø48,3 mm.

Decks are made of molded PP.

Roof made of 19 mm HDPE plates or impregnated pine wood.

Steps and ramps are made of Ecogrip 18 mm plates.

Infill made of 2,5 mm steel plates or 19 mm HDPE.

Net and climbing ropes made of Ø16 mm PP covered steel ropes.

Slides made of LDPE or stainless steel.

Floor heights 28, 58, 88, 118, 148 and 178 cm.

Height of net and climbing activities up to 224 cm.

Tested according to: DIN EN 1176-1:2017
DIN EN 1176-3:2017
EN 1176-1:2017
EN 1176-3:2017