

SWING ST0516






Device Specifications	
Safety zone	125,37 m
Length	6,45 m
Width	5,50 m
Total height	2,39 m
Free fall height	1,30 m
Age group	1-3/3-14 years
In accordance w/ EN standards	1176-1:2017
Weight of the heaviest part [kg]	18
Dimension of the biggest part [cm]	310x10x10
Availability of spare parts	Yes

R2



Minimal space



Material specification

- Galvanized and/or powder coated steel 100 x 100 mm construction;
- No sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- Stainless steel screws or screws covered with plastic caps;
- Top of the construction is secured with rubber caps;
- Stainless steel chain hooks;
- · Calibrated chain preventing fingers from getting stuck;
- Durable certified seats;

Additional information

- The equipment is certified by an accrediting organization or by certificate of conformity;
- Depth of foundations on a flat surface: 80/70/60 cm;
- The equipment is designed for public playgrounds;
- Available with different seat options: R2 cradle seat, R5 flat with back rest;

Surfaces:

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 1,30 m (A,B,C)

