



TECHNICAL DATA:


Not easy accessible device,
according to standard EN 1176-1:2017

Device dimensions:	3,51 x 2,96m
Device height:	3,35m
Minimum space:	6,91 x 5,96m
Falling area:	27,25m ²
Critical fall height:	1,36m
Foundations depth:	-0,60m

The device according to EN 1176-1:2012
Playground equipment and surfacing – Part 1:
General safety requirements and test methods.

Safety surfaces:
sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 200+100mm
- synthetic surface according to critical fall height

Top view with falling area



COMPONENTS:

Tower with roof, platform 0,90m	1 pc.
Tower without roof, platform 1,36m	1 pc.
Climbing wall 0,90m	1 pc.
Slide 1,36m	1 pc.
Fireman's pole 1,36m	1 pc.

MATERIALS:

Construction poles:	steel square profiles with a cross-section of 80x80mm, galvanized, powder coated in gray
Anchors:	galvanized steel
Flat decorative elements:	HDPE sheets, 15mm thick
Platforms, gangways:	waterproof formwork plywood, with non-slip layer, based on steel structure
Surface of slope slide:	stainless steel, 1,5 mm thick
Climbing walls:	Shuttering waterproof plywood, climbing grips, based on resins
Caps:	Plastic
Foundations:	concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o.
sp.k.
ul. Nowa 32
41-500 Chorzów, Poland

Certificateholder:
Producer:
Distributor:

GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A.
Saternus Production Sp. z o.o. sp. k.
Saternus Distribution Sp. z o.o. sp. k.