30030 SINGLE PENDULUM SWING



TECHNICAL DATA:

Top view with falling area

Device dimensions:	1,92m x 2,25m	740
Device height:	~2,40m	
Minimum space:	7,40 x 2,25m	
Critical fall height:	1,25m	55
Falling area:	16,65m ²	
Depth of foundations:	-0,60m	
The device according to EN 1176-1:2012 Playground equipment and surfacing – Part 1: General safety requirements and test methods		+2,40 +2,10
Safety surfaces: - turf/topsoil, sand, gravel, bark, synthetic surface - minimal thickness for loose particulate materials 200+100mm - synthetic surface according to critical fall height		

+0,45 +0,00 -0,60

MATERIALS:

Construction poles:	glued pine wood, rounded at the edges, coated with acrylic glaze	
Anchors:	steel galvanized	
Steel elements:	steel galvanized, powder coated	
Seats:	made of steel structure coated with rubber	
Decorative elements:	HDPE sheet	
Chain:	galvanized steel,	
Caps:	plastic	
Foundations:	concrete class min. C12/15	



Certificate beholder: Producer: Distributor:

 SATERNUS DISTRIBUTION Sp. z o.o. sp.k.
 GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, item 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A. Saternus Production Sp. z o.o. sp. k. Saternus Distribution Sp. z o.o. sp. k.